

Silicon carbide Power MOSFET 1200 V, 65 A, 59 mΩ (typ., TJ=150 °C) in an HiP247™ long leads package

Datasheet - production data





Figure 1: Internal schematic diagram



Features

- Very tight variation of on-resistance vs. temperature
- Very high operating junction temperature capability ($T_J = 200$ °C)
- Very fast and robust intrinsic body diode
- Low capacitance

Applications

- Solar inverters, UPS
- Motor drives
- High voltage DC-DC converters
- Switch mode power supplies

Description

This silicon carbide Power MOSFET is produced exploiting the advanced, innovative properties of wide bandgap materials. This results in unsurpassed on-resistance per unit area and very good switching performance almost independent of temperature. The outstanding thermal properties of the SiC material allows designers to use an industry-standard outline with significantly improved thermal capability. These features render the device perfectly suitable for high-efficiency and high power density applications.

Table 1: Device summary

Order code	Marking	Package	Packaging
SCTWA50N120	SCT50N120	HiP247™ long leads	Tube

Contents

1	Electrical ratings	3
2	Electrical characteristics	4
2.1	Electrical characteristics (curves).....	5
3	Package information	8
3.1	HiP247™ long leads package information	8
4	Revision history	10

1 Electrical ratings

Table 2: Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	1200	V
V_{GS}	Gate-source voltage	-10 to 25	V
I_D	Drain current (continuous) at $T_C = 25^\circ\text{C}$	65	A
I_D	Drain current (continuous) at $T_C = 100^\circ\text{C}$	50	A
$I_{DM}^{(1)}$	Drain current (pulsed)	130	A
P_{TOT}	Total dissipation at $T_C = 25^\circ\text{C}$	318	W
T_{stg}	Storage temperature range	-55 to 200	$^\circ\text{C}$
T_j	Operating junction temperature range		$^\circ\text{C}$

Notes:

(1)Pulse width limited by safe operating area.

Table 3: Thermal data

Symbol	Parameter	Value	Unit
$R_{thj-case}$	Thermal resistance junction-case	0.55	$^\circ\text{C/W}$
$R_{thj-amb}$	Thermal resistance junction-ambient	40	$^\circ\text{C/W}$

2 Electrical characteristics

($T_{CASE} = 25^\circ C$ unless otherwise specified).

Table 4: On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{DSS}	Zero gate voltage drain current	$V_{DS} = 1200 V, V_{GS} = 0 V$		1	100	μA
		$V_{DS} = 1200 V, V_{GS} = 0 V, T_J = 200^\circ C$		10		μA
I_{GSS}	Gate-body leakage current	$V_{DS} = 0 V, V_{GS} = -10 \text{ to } 22 V$			± 100	nA
$V_{GS(th)}$	Gate threshold voltage	$V_{DS} = V_{GS}, I_D = 1 mA$	1.8	3.0		V
$R_{DS(on)}$	Static drain-source on-resistance	$V_{GS} = 20 V, I_D = 40 A$		52	69	$m\Omega$
		$V_{GS} = 20 V, I_D = 40 A, T_J = 150^\circ C$		59		$m\Omega$
		$V_{GS} = 20 V, I_D = 40 A, T_J = 200^\circ C$		70		$m\Omega$

Table 5: Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	$V_{DS} = 400 V, f = 1 MHz, V_{GS} = 0 V$	-	1900	-	pF
C_{oss}	Output capacitance		-	170	-	pF
C_{rss}	Reverse transfer capacitance		-	30	-	pF
Q_g	Total gate charge	$V_{DD} = 800 V, I_D = 40 A, V_{GS} = 0 \text{ to } 20 V$	-	122	-	nC
Q_{gs}	Gate-source charge		-	19	-	nC
Q_{gd}	Gate-drain charge		-	35	-	nC
R_g	Gate input resistance	$f=1 MHz \text{ open drain}$	-	1.9	-	Ω




Table 6: Switching energy (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
E_{on}	Turn-on switching energy	$V_{DD} = 800 V, I_D = 40 A$ $R_G = 2.2 \Omega, V_{GS} = -5 \text{ to } 20 V$	-	530	-	μJ
E_{off}	Turn-off switching energy		-	310	-	μJ
E_{on}	Turn-on switching energy	$V_{DD} = 800 V, I_D = 40 A$ $R_G = 2.2 \Omega, V_{GS} = -5 \text{ to } 20 V$ $T_J = 150^\circ C$	-	670	-	μJ
E_{off}	Turn-off switching energy		-	334	-	μJ

Table 7: Reverse SiC diode characteristics

Symbol	Parameter	Test conditions	Min	Typ.	Max	Unit
V_{SD}	Diode forward voltage	$I_F = 20 A, V_{GS} = 0 V$ $I_F = 40 A, di/dt = 2000/ns$ $V_{DD} = 800 V$	-	3.5	-	V
t_{rr}	Reverse recovery time		-	55		ns
Q_{rr}	Reverse recovery charge		-	230	-	nC
I_{RRM}	Reverse recovery current		-	14	-	A

2.1 Electrical characteristics (curves)



Electrical characteristics

SCTWA50N120

Figure 8: Power dissipation




Figure 9: Gate charge vs gate-source voltage




Figure 10: Capacitance variations




Figure 11: Switching energy vs. drain current




Figure 12: Switching energy vs. junction temperature




Figure 13: Normalized $V_{(BR)DSS}$ vs. temperature










Figure 14: Normalized gate threshold voltage vs. temperature**Figure 15: Normalized on-resistance vs. temperature****Figure 16: Reverse conduction characteristics ($T_J = -50^\circ\text{C}$)****Figure 17: Reverse conduction characteristics ($T_J = 25^\circ\text{C}$)****Figure 18: Reverse conduction characteristics ($T_J = 150^\circ\text{C}$)**

3 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com.
ECOPACK® is an ST trademark.

3.1 HiP247™ long leads package information

Figure 19: HiP247™ long leads package outline



7395426_7.0

Table 8: HiP247™ long leads package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.90		5.15
D	1.85		2.10
E	0.55		0.67
F	1.07		1.32
F1	1.90		2.38
F2	2.87		3.38
G	10.90 BSC		
H	15.77		16.02
L	20.82		21.07
L1	4.16		4.47
L2	5.49		5.74
L3	20.05		20.30
L4	3.68		3.93
L5	6.04		6.29
M	2.25		2.55
V		10°	
V1		3°	
V3		20°	
DIA	3.55		3.66

4 Revision history

Table 9: Document revision history

Date	Revision	Changes
07-Jun-2016	1	First release
14-Sep-2016	2	Document status changed from preliminary to production data.
03-Apr-2017	3	Modified <i>Table 7: "Reverse SiC diode characteristics"</i> Modified <i>Figure 7: "Transfer characteristics"</i> , <i>Figure 15: "Normalized on-resistance vs. temperature"</i> , <i>Figure 16: "Reverse conduction characteristics ($T_J = -50 \text{ }^{\circ}\text{C}$)"</i> , <i>Figure 17: "Reverse conduction characteristics ($T_J = 25 \text{ }^{\circ}\text{C}$)"</i> and <i>Figure 18: "Reverse conduction characteristics ($T_J = 150 \text{ }^{\circ}\text{C}$)"</i> Minor text changes.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved